

FEATURES

CUMMINS DIESEL ENGINE
110% BUNDED SKID BASE WITH FORK POCKETS
CENTRE LIFTING POINT
IP23 STAMFORD UCI 274E1 ALTERNATOR
50 DEGREE RADIATOR
ABB 4 POLE MANUAL CIRCUIT BREAKER
IG200 CONTROL PANEL
ABB RD2 ADJUSTABLE RCD
BATTERY AND STARTER ISOLATOR
LOCKABLE ACCESS DOORS
1 X 32A OUTLET, 2 X 15A OUTLET
2.5MM STEEL HEAVY DUTY CANOPY

GENERATOR RATINGS

VOLTAGE	240/415
FREQUENCY	50
PHASE	3
POWER FACTOR	0.8
STANDBY AMPS	199A
STANDBY RATINGS (KW/KVA)	115kW/143kVA
PRIME RATINGS (KW/KVA)	104kW/130kVA
CONTINUOUS POWER RATINGS (KW/KVA)	81kW/101kVA

COMPLIANCE

AS3000, AS3008, AS3012, AS3017, AS3010, ISO3046

PRIME POWER (PRP): The total operating time at 100% Prime Power shall not exceed 500 hours per year. A 10% overload capability is available for a period of 1 hour within a 12 hour period of operation. Total operating time at the 10% overload power shall not exceed 25 hours per year.

STANDBY POWER RATING (ESP): Applicable for supplying emergency power for 1 hour from genset starting. No overload capability is available for this rating. Under no condition is an engine allowed to operate in parallel with the public utility at the standby Power rating.

CONTINUOUS POWER RATING (COP): Applicable for supplying utility power at a constant 100% load for an unlimited number of hours per year. No overload capability is available for this rating.



SOUND

NOISE LEVEL	74dBA @ 7M
-------------	------------

GENERATOR DATA

ENGINE	CUMMINS 6BTAA5.9-G2
ALTERNATOR	STAMFORD UCI274E1
AIR INTAKE SYSTEM	Turbocharged & Air-Air Cooled
FUEL SYSTEM	BYC A Pump, Direct Inj.
CYLINDER ARRANGEMENT	In-Line 6
DISPLACEMENT	5.9L
GOVERNOR TYPE	Electronically controlled actuator
RATED RPM	1500

DIMENSIONS

LENGTH	3,280MM
WIDTH	1,152MM
HEIGHT	1,992MM
DRY WEIGHT	1,900KG

FUEL SYSTEM

FUEL TANK CAPACITY	560L
100% PRIME LOAD	30.00 L/HR
75% PRIME LOAD	23.00 L/HR
50% PRIME LOAD	16.00 L/HR