

FEATURES

CUMMINS DIESEL ENGINE
110% BUNDED SKID BASE
LIFTING LUGS
IP23 STAMFORD UCI 274F1 ALTERNATOR
50 DEGREE RADIATOR
ABB 4 POLE MANUAL CIRCUIT BREAKER
IG200 CONTROL PANEL
ABB RD2 ADJUSTABLE RCD
BATTERY AND STARTER ISOLATOR
LOCKABLE ACCESS DOORS
1 X 32A OUTLET, 2 X 15A OUTLET
2.5MM STEEL HEAVY DUTY CANOPY

GENERATOR RATINGS

VOLTAGE	240/415
FREQUENCY	50
PHASE	3
POWER FACTOR	0.8
STANDBY AMPS	229A
STANDBY RATINGS (KW/KVA)	132kW/165kVA
PRIME RATINGS (KW/KVA)	120kW/150kVA
CONTINUOUS POWER RATINGS (KW/KVA)	93kW/116kVA

COMPLIANCE

AS3000, AS3008, AS3012, AS3017, AS3010, ISO3046

PRIME POWER (PRP): The total operating time at 100% Prime Power shall not exceed 500 hours per year. A 10% overload capability is available for a period of 1 hour within a 12 hour period of operation. Total operating time at the 10% overload power shall not exceed 25 hours per year.

STANDBY POWER RATING (ESP): Applicable for supplying emergency power for 1 hour from genset starting. No overload capability is available for this rating. Under no condition is an engine allowed to operate in parallel with the public utility at the standby Power rating.

CONTINUOUS POWER RATING (COP): Applicable for supplying utility power at a constant 100% load for an unlimited number of hours per year. No overload capability is available for this rating.



SOUND

NOISE LEVEL	74dBA @ 7M
-------------	------------

GENERATOR DATA

ENGINE	CUMMINS 6CTA8.3-G1
ALTERNATOR	STAMFORD UCI274F1
AIR INTAKE SYSTEM	Turbocharged & Aftercooled
FUEL SYSTEM	BYC P Pump, Direct Inj.
CYLINDER ARRANGEMENT	In-Line 6
DISPLACEMENT	8.3L
GOVERNOR TYPE	Electronically controlled actuator
RATED RPM	1500

DIMENSIONS

LENGTH	3,280MM
WIDTH	1,152MM
HEIGHT	1,992MM
DRY WEIGHT	2,500KG

FUEL SYSTEM

FUEL TANK CAPACITY	630L
100% PRIME LOAD	42.0 L/HR
75% PRIME LOAD	31.0 L/HR
50% PRIME LOAD	21.0 L/HR