

FEATURES

VOLVO DIESEL ENGINE
110% BUNDED SKID BASE WITH FORK POCKETS
LIFTING LUGS
IP23 STAMFORD UCI 274H1 ALTERNATOR
50 DEGREE RADIATOR
ABB 4 POLE MANUAL CIRCUIT BREAKER
IG200 CONTROL PANEL
ABB RD2 ADJUSTABLE RCD
BATTERY AND STARTER ISOLATOR
LOCKABLE ACCESS DOORS
1 X 32A OUTLET, 2 X 15A OUTLET
2.5MM STEEL HEAVY DUTY CANOPY

GENERATOR RATINGS

VOLTAGE	240/415
FREQUENCY	50
PHASE	3
POWER FACTOR	0.8
STANDBY AMPS	306A
STANDBY RATINGS (KW/KVA)	176kW/220kVA
PRIME RATINGS (KW/KVA)	160kW/200kVA
CONTINUOUS POWER RATINGS (KW/KVA)	124kW/155kVA

COMPLIANCE

AS3000, AS3008, AS3012, AS3017, AS3010, ISO3046

PRIME POWER (PRP): The total operating time at 100% Prime Power shall not exceed 500 hours per year. A 10% overload capability is available for a period of 1 hour within a 12 hour period of operation. Total operating time at the 10% overload power shall not exceed 25 hours per year.

STANDBY POWER RATING (ESP): Applicable for supplying emergency power for 1 hour from genset starting. No overload capability is available for this rating. Under no condition is an engine allowed to operate in parallel with the public utility at the standby Power rating.

CONTINUOUS POWER RATING (COP): Applicable for supplying utility power at a constant 100% load for an unlimited number of hours per year. No overload capability is available for this rating.



SOUND

NOISE LEVEL	76dBA @ 7M
-------------	------------

GENERATOR DATA

ENGINE	VOLVO TAD733GE
ALTERNATOR	STAMFORD UCI274H1
AIR INTAKE SYSTEM	Turbocharged & Air-Air Cooled
FUEL SYSTEM	Mech. Unit Pumps, Direct Inj.
CYLINDER ARRANGEMENT	In-Line 6
DISPLACEMENT	7.2L
GOVERNOR TYPE	Electronically controlled actuator
RATED RPM	1500

DIMENSIONS

LENGTH	3,620MM
WIDTH	1,292MM
HEIGHT	2,260MM
DRY WEIGHT	2,700KG

FUEL SYSTEM

FUEL TANK CAPACITY	780L
100% PRIME LOAD	43.60 L/HR
75% PRIME LOAD	34.10 L/HR
50% PRIME LOAD	24.00 L/HR

STAMFORD

ComAp
The heart of smart control

VOLVO
PENTA

VIKINGINDUSTRIAL.COM.AU

Materials and specifications are subject to change each quarter, specsheets are current to 12/03/2021
The International System of Units (SI) is used in this publication

1300 365 721

© 2021 VIKING INDUSTRIAL SALES PTY LTD
©2021 VIKING INDUSTRIAL PTY LTD