

FEATURES

VOLVO DIESEL ENGINE
110% BUNDED SKID BASE WITH FORK POCKETS
LIFTING LUGS
IP23 STAMFORD S4L1D-D41 ALTERNATOR
50 DEGREE RADIATOR
ABB 4 POLE MANUAL CIRCUIT BREAKER
IG200 CONTROL PANEL
ABB RD2 ADJUSTABLE RCD
BATTERY AND STARTER ISOLATOR
LOCKABLE ACCESS DOORS
1 X 32A OUTLET, 2 X 15A OUTLET
2.5MM STEEL HEAVY DUTY CANOPY

GENERATOR RATINGS

VOLTAGE	240/415
FREQUENCY	50
PHASE	3
POWER FACTOR	0.8
STANDBY AMPS	482A
STANDBY RATINGS (KW/KVA)	278kW/347kVA
PRIME RATINGS (KW/KVA)	252kW/315kVA
CONTINUOUS POWER RATINGS (KW/KVA)	195kW/244kVA

COMPLIANCE

AS3000, AS3008, AS3012, AS3017, AS3010, ISO3046

PRIME POWER (PRP): The total operating time at 100% Prime Power shall not exceed 500 hours per year. A 10% overload capability is available for a period of 1 hour within a 12 hour period of operation. Total operating time at the 10% overload power shall not exceed 25 hours per year.

STANDBY POWER RATING (ESP): Applicable for supplying emergency power for 1 hour from genset starting. No overload capability is available for this rating. Under no condition is an engine allowed to operate in parallel with the public utility at the standby Power rating.

CONTINUOUS POWER RATING (COP): Applicable for supplying utility power at a constant 100% load for an unlimited number of hours per year. No overload capability is available for this rating.



SOUND

NOISE LEVEL	76dBA @ 7M
-------------	------------

GENERATOR DATA

ENGINE	VOLVO TAD1341GE
ALTERNATOR	STAMFORD S4L1D-D41
AIR INTAKE SYSTEM	Turbocharged & Air-Air Cooled
FUEL SYSTEM	Electronic Fuel Injection System
CYLINDER ARRANGEMENT	In-Line 6
DISPLACEMENT	12.8L
GOVERNOR TYPE	Electronic
RATED RPM	1500

DIMENSIONS

LENGTH	3,910MM
WIDTH	1,454MM
HEIGHT	2,425MM
DRY WEIGHT	3,920KG

FUEL SYSTEM

FUEL TANK CAPACITY	1150L
100% PRIME LOAD	60.60 L/HR
75% PRIME LOAD	47.30 L/HR
50% PRIME LOAD	33.40 L/HR

STAMFORD

ComAp
The heart of smart control

VOLVO PENTA