

FEATURES

VOLVO DIESEL ENGINE
110% BUNDLED SKID BASE WITH FORK POCKETS
LIFTING LUGS
IP23 STAMFORD S4L1D-G41 ALTERNATOR
50 DEGREE RADIATOR
ABB 4 POLE MANUAL CIRCUIT BREAKER
IG200 CONTROL PANEL
ABB RD2 ADJUSTABLE RCD
BATTERY AND STARTER ISOLATOR
LOCKABLE ACCESS DOORS
1 X 32A OUTLET, 2 X 15A OUTLET
2.5MM STEEL HEAVY DUTY CANOPY

GENERATOR RATINGS

VOLTAGE	240/415
FREQUENCY	50
PHASE	3
POWER FACTOR	0.8
STANDBY AMPS	633A
STANDBY RATINGS (KW/KVA)	400kW/500kVA
PRIME RATINGS (KW/KVA)	360kW/450kVA
CONTINUOUS POWER RATINGS (KW/KVA)	253kW/316kVA

COMPLIANCE

AS3000, AS3008, AS3012, AS3017, AS3010, ISO3046

PRIME POWER (PRP): The total operating time at 100% Prime Power shall not exceed 500 hours per year. A 10% overload capability is available for a period of 1 hour within a 12 hour period of operation. Total operating time at the 10% overload power shall not exceed 25 hours per year.

STANDBY POWER RATING (ESP): Applicable for supplying emergency power for 1 hour from genset starting. No overload capability is available for this rating. Under no condition is an engine allowed to operate in parallel with the public utility at the standby Power rating.

CONTINUOUS POWER RATING (COP): Applicable for supplying utility power at a constant 100% load for an unlimited number of hours per year. No overload capability is available for this rating.



SOUND

NOISE LEVEL	74dBA @ 7M
-------------	------------

GENERATOR DATA

ENGINE	VOLVO TAD1345GE
ALTERNATOR	STAMFORD S4L1D-G41
AIR INTAKE SYSTEM	Turbocharged & Air-Air Cooled
FUEL SYSTEM	Electronic Fuel Injection System
CYLINDER ARRANGEMENT	In-Line 6
DISPLACEMENT	12.78L
GOVERNOR TYPE	Electronic
RATED RPM	1500

DIMENSIONS

LENGTH	4,225MM
WIDTH	1,460MM
HEIGHT	2,250MM
DRY WEIGHT	4,400KG

FUEL SYSTEM

FUEL TANK CAPACITY	900L
100% PRIME LOAD	73.6 L/HR
75% PRIME LOAD	57.5 L/HR
50% PRIME LOAD	40.5 L/HR

STAMFORD

ComAp
The heart of smart control

VOLVO PENTA