

FEATURES

VOLVO DIESEL ENGINE
110% BUNDED SKID BASE WITH FORK POCKETS
LIFTING LUGS
IP23 STAMFORD UCI 224G1 ALTERNATOR
50 DEGREE RADIATOR
ABB 4 POLE MANUAL CIRCUIT BREAKER
COMAP MRS16 CONTROL PANEL
ABB RD2 ADJUSTABLE RCD
BATTERY AND STARTER ISOLATOR
LOCKABLE ACCESS DOORS
1 X 32A OUTLET, 2 X 15A OUTLET
2.5MM STEEL HEAVY DUTY CANOPY

GENERATOR RATINGS

VOLTAGE	240/415
FREQUENCY	50
PHASE	3
POWER FACTOR	0.8
STANDBY AMPS	130A
STANDBY RATINGS (KW/KVA)	75kW/94kVA
PRIME RATINGS (KW/KVA)	68kW/85kVA
CONTINUOUS POWER RATINGS (KW/KVA)	53kW/66kVA

COMPLIANCE

AS3000, AS3008, AS3012, AS3017, AS3010, ISO3046

PRIME POWER (PRP): The total operating time at 100% Prime Power shall not exceed 500 hours per year. A 10% overload capability is available for a period of 1 hour within a 12 hour period of operation. Total operating time at the 10% overload power shall not exceed 25 hours per year.

STANDBY POWER RATING (ESP): Applicable for supplying emergency power for 1 hour from genset starting. No overload capability is available for this rating. Under no condition is an engine allowed to operate in parallel with the public utility at the standby Power rating.

CONTINUOUS POWER RATING (COP): Applicable for supplying utility power at a constant 100% load for an unlimited number of hours per year. No overload capability is available for this rating.



SOUND

NOISE LEVEL	72dBA @ 7M
-------------	------------

GENERATOR DATA

ENGINE	VOLVO TAD530GE
ALTERNATOR	STAMFORD UCI 224G1
AIR INTAKE SYSTEM	Turbocharged & Air-Air Cooled
FUEL SYSTEM	Mech. Unit Pumps, Direct Inj.
CYLINDER ARRANGEMENT	In-Line 4
DISPLACEMENT	4.8L
GOVERNOR TYPE	Electronically controlled actuator
RATED RPM	1500

DIMENSIONS

LENGTH	2,460MM
WIDTH	1,000MM
HEIGHT	1,733MM
DRY WEIGHT	1,850KG

FUEL SYSTEM

FUEL TANK CAPACITY	160L
100% PRIME LOAD	19.30 L/HR
75% PRIME LOAD	15.10 L/HR
50% PRIME LOAD	10.70 L/HR

STAMFORD

ComAp
The heart of smart control

VOLVO
PENTA